

• S P E C I F I C A T I O N S •

- VAULT BODY TWO $\frac{1}{2}$ " STEEL PLATES WELDED TO FORM THE VAULT SIDE WALLS, BACK AND TOP WITH SPACE BETWEEN PLATES CONCRETE FILLED.
- DOOR $3\frac{1}{2}$ " VAULT DOOR WITH (2) 4-TUMBLER KEY CHANGING, BANK TYPE COMBINATION LOCKS WITH SHIELDED DIALS.
- TIMELOCK 3-MOVEMENT TIMELOCK FURNISHED AS STANDARD EQUIPMENT.
- ALARM SYSTEM . . . VAULT DESIGNED TO RECEIVE TWO SOUND WAVE RECEIVERS, (2) THERMOs ON EACH OF DOOR & DOOR CONTACT. FURNISHED ONLY WHEN SPECIFIED. (OPTIONAL EXTRA)
- ELECTRICAL TWO FLUORESCENT LIGHTS MOUNTED ON CEILING OF VAULT IN FULL WIDTH FIXTURE. CONDUIT STUBS OUT PROVIDED.
- INSTALLATION . . . DOOR & FRAME CAN BE REMOVED FROM VAULT STRUCTURE TO REDUCE THE OVERALL DEPTH OF THE UNIT TO $32\frac{1}{16}$ ". FOUR HOLES PROVIDED IN BOTTOM PLATE FOR SECURING UNIT.
- SECURITY MEETS INSURANCE RATING BOARD SPECIFICATIONS CLASS 6B VAULT
- FINISH VAULT EXTERIOR & INTERIOR PRIME PAINTED. FINISH COLOR AFTER INSTALLATION (NOT BY DIEBOLD). TRIM FRAME, DOOR FRONT, HINGE COVERS, & BOLTWORK COVER IS STAINLESS STEEL. DOOR EDGE & JAMBS ARE POLISHED STEEL.
- WEIGHT OF UNIT . . . APPROXIMATELY 10,000 LBS. CRATED 10,500

OPTIONAL FEATURES & INTERIOR QUESTIONNAIRE

- RIGHT SWING VAULT DOOR LEFT SWING VAULT DOOR
 - ALARM EQUIPMENT (FOR CONNECTION TO BANKS PRESENT ALARM SYSTEM)
 - ALARM EQUIPMENT (NEW #16-16 OR #115-35) CONTROL CABINET IN SECURITY HOUSING.
- CONSTRUCTION & THICKNESS OF FLOOR TO SUPPORT VAULT IS _____
 (VAULT MUST BE BOLTED TO CONCRETE FLOOR TO RECEIVE ALARM CERTIFICATE)

