





ISM Advantage MK 2

TL-15

The ISM Advantage is the new generation of small but very tough jewellery/money safes which offer not only attractive design but also security features which have been tested and approved by the Underwriters Laboratories. The U.L. have certified the ISM Advantage for a TL-15 label.



Door:

The door is constructed of 40mm (1½") steel plate. In addition, special hardened steel ball bearings are placed in strategic locations to resist drilling attacks.

Body:

The body is constructed of 25mm (1") steel plates. The construction employs advanced welding methods to form a jointless outer shell of tough steel plate. The welds are hand ground to give a smooth, uninterrupted finish.

Lock:

The Advantage is equipped with a three wheel combination lock with 1,000,000 possible combinations. The combination dial and dial ring are satin nickel finished.

Boltwork:

The ISM Advantage is equipped with a three way active boltwork. By turning the handle to the locking position the bolts are extended in three directions. Fixed bolts lock the hinge side of the door. The entire mechanism is protected by a special plating process preventing oxidation and rust.

Relocking Mechanism:

The lock is protected by a tempered glass plate. If attacked by tools or explosives it will shatter into pieces thus activating the relocking mechanism. The relocker cannot be pulled back as it is equipped with a self-locking pin.

Interior Fittings:


Adjustable shelves are available for arranging the safe interior.

Finish:


A modern stainless capstan wheel and an anodized aluminium facia panel complement the durable paint finish standard on all ISM Security Equipment.

ISM Advantage MK2 TL-15


Dimensions and Weights




ER1414



ER2416



ER2020



ER3820

Model	Inside Dimensions (mm/in)			Outside Dimensions (mm/in)			Volume (Lt/Cu In)	Est. Weight (Kg/Lbs)
	Height	Width	Depth	Height	Width	Depth*		
ER1414	356	356	305	406	406	451	39	255
	14	14	12	16	16	17 ³ / ₄	2352	560
ER2416	610	406	406	660	457	552	100	450
	24	16	16	26	18	21 ³ / ₄	6144	990
ER2020	508	508	508	559	559	654	131	500
	20	20	20	22	22	25 ³ / ₄	8000	1100
ER3820	965	508	508	1016	559	654	249	700
	38	20	20	40	22	25 ³ / ₄	15200	1540

* Add 2" (0.51m) to outside depth for handle.

ISM

