

INFINITY

TRTL-30x6

HIGH SECURITY SAFES

SPECIFICATIONS TRTL-30X6

DOOR

- Overall thickness 7"
- 3 1/2" aluminum casting which incorporates a 1 1/4" layer of 9.7 hard quartzite nuggets
- Copper framing resists torch attack at strategic areas
- Additional layer of 1 1/2" high strength composite materials

BODY

- 3 1/2" aluminum bell casting incorporates 1 1/4" 9.7 hard quartzite nuggets
- Copper framing resists torch attack at strategic areas
- Additional layer of 1 1/2" high strength composite materials

BOLTWORK

- Multi-directional movable boltwork (top, bottom, front)
- Fixed rear boltwork
- 1 1/2" thick bolts with 1 1/2" throw

LOCKING DEVICES

- Dual-control locking system
- Group 1 manipulation proof UL rated combination lock
- High security key lock (12 levers)

RELOCKING DEVICES

- Minimum of three randomly located non retractable relockers
- One live relocker

RATING

- UL TRTL-30X6
- One hour YUS fire rating

MODEL	INTERNAL (In.)			EXTERNAL (In.)			CUBIC CAPACITY (ft ³)	WEIGHT
	H	W	D	H	W	D		
2618	26	18	18	35	27	29 1/2	4.87	1896
3320	33	20	22	42	29	33 1/2	8.40	2645
4520	45	20	22	54	29	33 1/2	11.45	3086
5220	52	20	22	61	29	33 1/2	13.24	3527
6422	64	22	25	73	31	36 1/2	20.37	4497
7036	70	36	26	79	45	37 1/2	37.91	6283

MEGASAFE

HIGH SECURITY SAFES