

ORIGINAL

SAFE & VAULT INC.

SAFE DOOR

Constructed of high strength composite materials developed by Original Safe & Vault Inc. With an overall door thickness of 6.75 inches, Original has included yet another proprietary super alloy in the plate surrounding the inner door lining.

SAFE BODY

Constructed of the same high strength composite materials with an overall thickness of 3.5 inches. Original's anti-peel Zee Bar system is fastened to the inner and outer structure of the body.

BOLT WORK

Moving and fixed bolts are a full 1.5 inches in diameter. Receiver cups are welded to the super alloy inner body lining.

DUAL LOCKING

Locking by a Group 2 combination lock with over one million combinations and a high security key lock. The locks are interchangeable. Electronic locks are optional.

LOCKING MECHANISM


Lock mechanism is protected by a random relocking system. A tempered glass trigger will activate the relocking system in the event of an attack.

UL TL 30X6 JEWELERS

Original Safe & Vault Co. reserves the right to alter any specification and make necessary improvements in the interest of providing maximum security. Shelves are removeable and adjustable. Right handle door available.

THE JEWELERS TL30X6 fire and theft resistant safe features six sided protection. The safe has advanced design features to protect against conventional tools, hammers, chisels, wedges, drills and explosive attacks. The Original Safe & Vault Jewelers UL rated TL30X6 will protect your valuables like no other safe in its class.

Options include right handle door, private interior compartment with key or combination lock, additional shelves and a 144 hour time clock.



TL30X6 MODEL	INTERNAL			EXTERNAL			CUBIC CAPACITY	QUANTITY SHELVES	WEIGHT (lbs.)	DOOR SWING	
	H	W	D	H	W	D				A	B
2217	22	17	16	29	24	27	3.47	1	1345	49.00	44.00
2618	26	18	18	33	25	29	4.87	1	1590	50.50	44.75
3320	33	20	18	40	27	29	6.88	2	2035	54.50	49.50
3324	33	24	19	40	31	30	8.24	2	2095	58.25	57.25
4520	45	20	18	52	27	29	9.37	3	2549	54.50	49.25
5220	52	20	20	59	27	31	12.15	3	3168	55.76	49.50
5224	52	24	19	59	31	30	13.25	3	3300	58.25	57.25
6422	64	22	24	71	29	35	19.55	4	3990	62.00	53.00
6434	64	34	20	71	41	31	25.18	4	4707	69.00	77.00
7036	70	36	26	77	43	37	37.91	5	5805	77.00	81.25

ADD ADDITIONAL 2in. FOR HANDLE & HINGES