

ORIGINAL

SAFE & VAULT INC.

Titan TL30 Series




- **High Security UL Rated TL30** — Potentially insures up to \$1/2 Million.
- **Burglary Resistant** — Protects against powerful tools such as drills, chisels, sledgehammers, wedges, power saws, carbide disc cutters, and explosive attacks.
- **Fire Resistant** — 350 Degree, Two Hour Fire Resistant Rating. Manufacturer tested at temperatures up to 1850 Degrees.
- **Safe Door** — An impressive 6.75 inches thick, constructed of a high strength blend of PSI cement, including super alloy manganese plating.
- **Safe Body** — Constructed of the same high strength blend of PSI cement with an overall body of 3.5 inches.
- **Bolt Work** — Massive 1.5 inch hardened steel side bolts, chrome fixed bolts, and the all important top and bottom locking steel bolts.
- **Dual Locking** — Sargent and Greenleaf UL Rated Group 2M High Security Chrome Combination Lock and High Security Key Lock.
- **Locking Mechanism** — Protected with random relocking systems. A tempered glass trigger will activate the relocking systems in the event the safe is attacked.
- **Door Hardware** — Chrome Pull Handle and Chrome Tri-Spoke Turn Handle.
- **Shelves** — Easy slide in shelf clips for adjustable shelving.
- **Options** — Left hand swing safe, electronic locks, custom manufactured safes, wooden interiors, additional shelves, and private interior compartments.

Built to withstand intense fire and burglary attack, the Titan by Original is the benchmark of quality in its class. Jewelers, corporate retail stores, and homeowners alike will gain peace of mind with its high security protection. Dependable and affordable, the Titan by Original is a great investment for those that need maximum security at a minimum cost.

The safe has advanced design features such as its world class mechanism door, super alloy manganese plating, and its anti-peel Zee Bar structure which is solidified with a highly developed blend of PSI cement. The Titan by Original will protect your valuables like no other safe in its class.

Safe Model	Internal Dimensions (inches)			External Dimensions (inches)			Volume (Cubic Capacity)	Shelves	Door Swing (inches)		Weight (lbs.)
	H	W	D	H	W	D			A	B	
ULTL30											
2014	20	14	12	27	21	23	1.94	1	41.54	37.2	977
2514	25	14	12	32	21	23	2.43	1	41.54	37.2	1067
2217	22	17	16	29	24	27	3.47	2	48.23	43.07	1342
2618	26	18	18	33	25	29	4.87	2	51.22	45.03	1496
3320	33	20	18	40	27	29	6.88	3	53.23	49.05	1936
3324	33	24	19	40	31	30	8.24	3	58.23	57.04	1980
4520	45	20	18	52	27	29	9.37	4	53.23	49.06	2392
5220	52	20	20	59	27	31	12.03	5	55.6	49.06	3003
5224	52	24	19	59	31	30	13.72	5	58.62	57.05	3036
5620	56	20	20	63	27	31	12.96	5	55.7	48.8	3102
5625	56	25	19	63	32	30	15.39	5	59.3	59.3	3525
6422	64	22	24	71	29	35	19.55	5	61.6	53.03	3727
6434	64	34	20	71	41	31	25.18	5	69.6	77.04	4411
7036	70	36	26	77	43	37	37.91	6	77.6	81.02	5412



Add an additional 2 inches to depth for handles and hinges.